


1.0 Ton Electric Stacker Lifting Height: 1600-1950mm



Advantages

Configuration and Performance

- Separately excited motor, Strong climbing ability.
- O High strength forks.
- Built-in charger is standard.
- Automatic lifting limit, Motor and battery life extension.

Safety

- O Stepless speed control system, safe and quiet.
- O Controller with Multiple automatic protection
- Emergency reversing device/Emergency brake



Built-in charger

Free-maintained battery

Adjustable forks at three choices



TOP1 FORKLIFT MANUFACTURER AND SALER IN CHINA FOR CONSECUTIVE 24 YEARS

Туре	Lift height (mm)	Mast type	Outside width between legs (mm)	
CDD10-090	1600/1950	SINGLE STAGE	1120/1270/1420	970/1120/1270



CDD10-090

Feature		
Model		CDD10
Configuration No.		090
Туре		Straddle
Mast type		Single stage
Load capacity	kg	1000
Load center	mm	600
Wheel base	mm	1134
Operating type		Walkie
Wheels		
Wheels type		PU
Wheel quantity Driving wheel/Balance wheel/Bearing wheel		1/1/4
Dimension		
Standard lift height	mm	1600/1950
Max.extend height	mm	2055/2405
Mast lowered height	mm	2055/2405
Lowered fork height	mm	55
Fork size(length/width/thickness)	mm	1070/100/40
Overall length	mm	1640
Overall width	mm	940
Outside width between forks	mm	200-812
Inside width between forks	mm	0-612
Min.Turning radius	mm	1344
Min. Aisle width for pallets 800×1200	mm	1894
Min. Aisle width for pallets 1000×1200	mm	1936
Min.ground clearance	mm	50
Performance		
Travel speed, laden/unladed	km/h	3/3.5
Lift speed, laden/unladed	mm/s	130/230
Lowering speed, laden/unladed	mm/s	130/230
Gradeability,laden/unladed	%	5/7
Electrical configuration		
Drive motor/Lift motor/Steering motor	kW	DC0.63/DC2.0
Battery voltage	V	24
Battery capacity	Ah	70
Brake		Electromagnetic/Regenerative
Controller		HELI(Options CURTIS)
Weight	l lu	
Battery weight	kg	48
Service weight with battery	kg	458

^{*} Details of specifications and equipment are based on information available at time of printing and may change without notice.



Click Here to visit our website

Email us: sales@ncfork.com.au

Call us: <u>0437 804 082</u>